

PHOTONIS

NIGHT VISION

XD-4™

XD-4™ Image Intensifier

The introduction of the XD-4™ technology sets the new European standard for low-light-level imaging. XD-4™ Image Intensifiers perform extremely well in all environmental conditions.

Its broad spectral sensitivity range results in a perfect picture.

New production technology resulted in improved performance of the Signal-to-Noise Ratio (SNR), the Modulation Transfer Function (MTF) and Resolution. Add to this features like the small halo and the extended lifetime and you will be convinced of its unique performance. The XD-4™ is also available with an Auto-Gating power supply unit.



Resolution				
	Minimum	Typical	Maximum	Unit
Limiting resolution	57	64		lp/mm
High light level resolution (>200 lux)	20*			lp/mm
MTF (Modulation Transfer Function)				
	Minimum	Typical	Maximum	Unit
2.5 lp/mm		92		%
7.5 lp/mm		80		%
15 lp/mm		58		%
25 lp/mm		45		%
30 lp/mm		35		%
Signal-to-noise Ratio (SNR)				
	Minimum	Typical	Maximum	Unit
Signal-to-noise Ratio (@ 108 µlx)	20	23		
Auto-Gating Power Supply Unit (optional)				
	Minimum	Typical	Maximum	Unit
Luminance dynamic range	1×10^{-6}		5×10^4 **	lux
Input voltage	2	2.7	3.5	Volt
Input current		16	26	mA
Other Technical Data				
	Minimum	Typical	Maximum	Unit
Phosphor	P22 (also available in P43)			
MTTF	10.000			hours
Halo		0.8		mm
Gain at 2×10^{-5} lx	10.000		18.000	cd/m ² /lx
Gain at 2×10^{-6} fc	30.000		55.000	fL/fc
Max. Output Brightness	2		17	cd/m ²
E.B.I.		0.15	0.25	µlx
Output uniformity 2850K		2:1	3:1	
Weight		80	95	grams
Shock resistance	500			g

* With Auto-Gating 50 lp/mm

** When fitted with Auto-Gating

PHOTONIS

For more information, please visit www.photonis.com

PHOTONIS Netherlands B.V.
Dwaziewegen 2
9301 ZR RODEN
The Netherlands

PHOTONIS France SAS
Avenue Roger Roncier
19100 Brive La Gaillarde
France

Sales Night Vision contact information:

T: +31 (0)505 01 88 08
F: +31 (0)505 01 14 56

E: nightvision@photonis.com